

NOVA 4 C+R

Durable 4000 lumen rechargeable work light

NOVA 4 C+R is an all-round LED floodlight designed for professionals.

The DUAL SYSTEM makes it possible to use the work light with 5 m rubber power cable or without the cable, providing higher flexibility on the work site. It only takes a second to connect the power cable – or disconnect when a cordless work light is needed.

Designed to perform consistently in tough work environments, NOVA 4 C+R is extremely durable and resistant to water and dust (IP67). Equipped with an integrated carrying handle and flexible bracket for easy transportation and mounting on a SCANGRIP TRIPOD, the NOVA 4 C+R work light is versatile and suited for various working environments. For those seeking diffused light, a diffuser can be acquired as an add-on. SCANGRIP provides a wide range of accessories to increase the functionality of the work light for all types of working situations.



Powered by a high efficiency multi-LED design of 90 LEDs, NOVA 4 C+R provides up to 4000 lumens. Along with the option to adjust the light output in five different levels, the handlamp also includes separate indicators for runtime and battery life, allowing you to easily track the operating time and remaining battery power. The OPTILight setting delivers the required illuminance (LUX) in a typical work situation, ensuring optimized light and runtime with a simple touch. This work light provides a constant lumen output performance measured according to the European standard EN 13032-1.



DUAL 2 in 1 SYSTEM

NOVA 4 C+R	
Product number	03.6204
Light source	High efficiency multi-LED design with 90 LEDs
Luminous flux, lumen	400-4000
OPTILight setting	200 lux@2 m
Adjustable light output	6 levels
Beam angle	110°
CRI	Ra > 80
CCT	5700 K
Operating time max. / min. lumen, h	2/18
Operating time OPTILight, h	3.5
Charging time, h	3
Battery	18.5 V / 2600 mAh Li-ion
Verified no. of charging cycles	Min. 1000
Protection class	IP67
Rough service	Yes
Impact protection	IK07
Impact resistance	2 m
Cable	5 m / 2 x 0,75 mm ² H05RN-F
Operating voltage AC	-
Charging voltage/current DC	24 V / 1.5 A
Power consumption	25 W
Charger incl.	Yes
Operating temperature	-10 to +40 °C
Dimensions	235 x 82 x 235 mm
Net weight	1.98 kg



03.6204 NOVA 4 C+R



03.5441 NOVA 4K C+R
Previous version

PRODUCT IMPROVEMENTS

- 14 % efficiency improvement
- 44 % recycled material
- OPTILight functionality
- Dedicated buttons for on/off and brightness levels
- Easier cable connectivity and improved bracket design
- Double temperature surveillance to protect the lamp and battery
- Min. 1000 charging cycles
- Rough service certified
- Warranty extended from 3 to 5 years
- New colour scheme

A pioneering approach that focuses on reinventing the design and functionality of LED work lights and optimizing energy efficiency to the utmost. With a focus on sustainability, traditional standards are rethought, and boundaries are pushed to extend the lifespan of lighting solutions.



Keep the light you love.



Spare parts available