

TOWER 12 CONNECT

12000 lumens floodlight with integrated tripod for power tool battery packs

TOWER 12 CONNECT is the market's most powerful floodlight with an integrated heavy-duty tripod, powered by standard power tool battery packs. Designed for rough outdoor use, it withstands demanding jobsite conditions while remaining lightweight and easy to transport.

The integrated tripod extends from 1.5 m to 3.0 m for effective lighting of large indoor and outdoor areas. Three adjustable LED heads and a 360° tilting base offer directional, 360°, or downlight illumination with 6 brightness levels (10–100 %).

Setup is fast and simple: unlock it, raise the tower, and the legs drop smoothly into position due to the built-in shock absorber. Use the mounting holes to secure ground spikes for extra stability on uneven surfaces; without spikes, it remains stable up to a 15 % tilt. The LED heads can be folded inwards to protect them during transport, and a carry bag is provided for easy storage.



The OPTILight setting delivers the required illuminance (LUX) in a typical work situation, ensuring optimized light and runtime with a simple touch. This work light provides a constant lumen output performance measured according to the European standard EN12464-2.

BATTERY, CHARGER, CONNECTORS AND POWER SUPPLY ARE SOLD SEPARATELY

SCANGRIP CONNECTORS for 18 V/20 V battery pack

AEG - 03.6158C
BERNER - 03.6156C
BOSCH/AMPHARE - 03.6140C
BOSCH GREEN - 03.6141C
DEWALT - 03.6142C
EINHELL - 03.6143C
FEIN - 03.6144C
FESTOOL - 03.6153C
FLEX - 03.6145C
HAZET - 03.6146C
HIKOKI - 03.6147C
HILTI - 03.6157C
INGERSOLL - 03.6152C
MAKITA - 03.6148C
MILWAUKEE - 03.6149C
PANASONIC - 03.6156C
RIDGID - 03.6154C
RUPES - 03.6159C
SNAP-ON - 03.6151C
WÜRTH - 03.6150C

Accessories



TECHNICAL SPECIFICATIONS

3 x 160 LEDs
1200–12000 lm (6 steps)
OPTILight setting: 200 lux at 4m
1–10 h operating time @18 V 5.2 Ah battery
Compatible with METABO / CAS battery system
18 V and all other 18 V / 20 V battery packs by using the SCANGRIP CONNECTOR
50 min. 1200 lm (backup battery)
80 W
IP65 / IK08
–10 to +40 °C / +14 to +104 °F operating temperature
H 1555 to 3020 x Ø 1600 mm /
H 61.22 to 118.90 x Ø 63 in
14.86 kg / 32.76 lbs



A pioneering approach that focuses on reinventing the design and functionality of LED work lights and optimizing energy efficiency to the utmost. With a focus on sustainability, traditional standards are rethought, and boundaries are pushed to extend the lifespan of lighting solutions.




Compatible with METABO/CAS battery system
For METABO/CAS no connector is required

TOWER 12 CONNECT
Item no. 03.6214C



JUST CONNECT
Add the connector matching your 18 V / 20 V battery pack



EU DESIGN PATENT PEND.

SCANGRIP.COM

ORIGINAL
SCANGRIP



SINCE 1906

5
years
warranty

Read terms and register on
scangrip.com to activate
your warranty